


TM-MASTS

TACTICAL TELESCOPIC PUSH-UP MASTS FOR LIGHT TOP LOADS





PRODUCT PAGE

TM-MASTS

Lightweight telescopic TM-masts are push-up masts for heights up to 7,6 meters (24.9 ft) and for 2–5 kg (up to 11 lb) top loads. Mast sections are pushed out and locked with friction locks one by one.

TM-masts are made of glass fibre composite material. Designs can be customised according to customer's specifications and requirements. Mast tube colour is dark green. Other tube colours are available at request. TM-masts can be supplemented with a wide range of mounting kits for vehicles and shelters.

ACCESSORIES AND ANCILLARIES

- variety of mast base supports for unguyed mast
- guying accessories
- vehicle mounting kits
- antenna brackets
- variety of mast base supports for unguyed mast

Standard TM mast systems

MAST TYPE	TM51	TM58	TM58
EXTENDED HEIGHT (M/FT)	4/13.1	6.5/21.3	7.6/24.9
TRANSPORTATION LENGTH (M/FT)	1.2/3.9	1.35/4.4	1.8/5.9
VERTICAL TOP LOAD (KG/LB)	5/11	5/11	5/11
WIND AREA C _{XA} (M ² /FT ²)	0.1/1	0.1/1.1	0.1/1.1
OPERATIONAL WIND SPEED (M/S / MPH)	15/34	15/34	15/34
MAST WEIGHT (KG/LB)	2.5/6	3.8/8	5/11
ACCESSORIES WEIGHT (KG/LB)	OPTIONAL	OPTIONAL	OPTIONAL

Masts listed above are examples. Other lengths with different top load specifications are available at request.

Mastsystem Int'l Oy's quality – and environmental management system fulfils the requirements of ISO 9001, ISO 14001 and AQAP 2110 standards. Masts and accessories have been proven to meet the environmental requirements in accordance with the MIL-STD 810 and DEF STAN 00-35.



CONTACT! Is the North American distributor for Mastsystem Int'l Oy:

Contact Corporation
 1818 Roberts Street
 Winchester, VA 22601, USA
 T: 540-722-8716
 F: 540-722-8717
 ggroah@contactcorp.net
 www.contactcorp.net

